




EN



# APP MANUAL

<b>Main screen</b> .....	3	Multiple selections.....	18
<b>Login</b> .....	4	Setup.....	19
<b>Create account</b> .....	5	Type of system.....	20
<b>Account</b> .....	6	Type of control.....	20
Account settings.....	6	Away offset.....	20
Account data.....	7	Programming.....	21
Language selection.....	7	Daily programming.....	21
Home management.....	8	Copy program.....	22
Add new home.....	8	Add / Modify program.....	23
Home settings.....	9	Time setting.....	23
Association to Smartbox.....	9	Records.....	24
Geolocation.....	10	<b>Energy Meter</b> .....	25
Force away mode.....	11	Main screen.....	25
<b>Install new devices</b> .....	12	Instantaneous consumption.....	25
Thermostat association from APP.....	12	Setup.....	25
Thermostat association in room.....	13	Records.....	26
Energy Meter Association from App.....	14	<b>Help</b> .....	27
Energy Meter Association in Room.....	15	<b>Support</b> .....	30
<b>Thermostat</b> .....	16		
Main screen.....	16		
Override / Switch off.....	17		
Thermostat options.....	17		

The APP allows the user to configure, program and access consumption statistics by using a simple and intuitive interface.




## LOGIN

The login screen features a dark blue header with the PERRY logo. Below the header, there are two input fields: 'Email' with a magnifying glass icon and 'Password' with a lock icon. A blue 'SIGN IN' button is positioned below the password field. Underneath the button is a 'REMEMBER ME' section with a toggle switch. At the bottom, there are two links: 'New user, sign up here!' and 'I forgot my password'. Callouts with blue lines point to the email field (labeled 'E-mail address'), the password field (labeled 'Password'), the 'SIGN IN' button (labeled 'Login button'), the 'REMEMBER ME' toggle (labeled 'If selected, it allows you to access without entering your credentials once again'), the 'New user, sign up here!' link (labeled 'Registration'), and the 'I forgot my password' link (labeled 'Recover password').

## RECOVER PASSWORD

The recover password screen has a dark blue header with a 'BACK' arrow and the PERRY logo. The main content area features a background image of a modern building at dusk. A text message reads: 'Don't worry, just provide your registration email so that you can start the password reset process'. Below this is an 'Email' input field with a magnifying glass icon. At the bottom, there is a blue 'RESET PASSWORD' button.



The creation and registration of an account to manage the Wi-Fi programmable thermostat is totally free of charge.

To do so you must have an operating e-mail address to access to complete registration by means of a verification e-mail.

Several devices (tablet, PC, smartphone) can use the same account and control the appliances associated to it.


Changes performed by one device will be shown on all the devices which have access to the account.

You must accept the terms and conditions of use and the privacy policy to be able to register.

Find the **Perry Programmable Thermostat App** in stores or take a picture of the QR Code for the operating system which your device uses.




INITIAL SCREEN



Account settings

ACCOUNT SETTINGS



Close tab


Account data

Home management


Support

Logout from account


ACCOUNT DATA




LANGUAGE SELECTION




HOME MANAGEMENT




ADD NEW HOME



## HOME SETTINGS




## ASSOCIATION TO SMARTBOX



Geolocation allows you to automatically reduce the set temperature when the user is not home. The system does not require any intervention as it uses the GPS function of your smartphone. The temperature reduction can be set by the user (to a maximum of 5°C), it can be activated or deactivated and it can be modified manually.


- Select the home from the tab in the account settings and click geolocation to activate the function.
- Then select the position of your home on the map and save it.
- Set the distance beyond which the system will consider you away from home.



Enable geolocation


Position of home on the map

Setting distance from home to activate temperature reduction




- There are two ways to intervene manually:
  1. With the APP by selecting the home on the main screen
  2. By pressing any button on the programmable thermostat. This allows the system to know someone is home and it will set the "AT HOME" mode.

**NB:** intervening on the device with the APP, such as rising or lowering the temperature, does not modify the AT HOME / AWAY status



## PERRY APP


By pressing the "Install" button on the main screen you access the installation menu and you may select the type of device



## Install new devices



### THERMOSTAT ASSOCIATION FROM APP

By following the wizard you may quickly associate the thermostat by pressing the search button and the two buttons displayed on the thermostat for 3 seconds




## THERMOSTAT ASSOCIATION IN ROOM

Instead of association via APP, you may associate the thermostat by pressing the association key on the Smartbox for 3 seconds and the two external buttons on the thermostat for 3 seconds.




Following dissociation of the programmable thermostat (by means of the procedure described in the relative manual), simply select the device on the main screen of the App by means of the multiple checkbox and press "Delete".

By pressing the "Install" button on the main screen you access the installation menu and you may select the type of device



## ENERGY METER ASSOCIATION FROM APP



To associate the Energy Meter via APP, press the search key and use a paper clip to press the key on the meter.

... at the top of the device (see image above). You can check that it has been linked by looking at the device **LED**.



### LED indicator states

- **Unlinked:**  
LED off
- **Correctly linked:**  
LED blinks every two seconds and a half.
- **Linked but lost:**  
LED blinks every half second. This can happen for example when the gateway is unpowered. Once the power meter and the gateway reestablish communication, it will be linked automatically.




## ENERGY METER ASSOCIATION IN ROOM

Instead of association via APP, you may associate the Energy Meter by pressing the association key on the Smartbox for 3 seconds and the button on the Energy Meter using a paper clip.



## MAIN SCREEN



Programmable thermostat management

Click to manage the device

Name of room

Detected temperature

Help

Install new devices

Account settings


Home selection

Energy Meter management (optional accessory)

Selection

Configuration and other functions

## MULTIPLE SELECTIONS



Device selected.

The selection of one or more devices allows to delete or set up simultaneously the options:

- Temperature
- Switch off
- Program
- Setup

Configuration and other functions

Delete selected devices

## OVERRIDE / SWITCH OFF

Selected device: Bedroom

Temperature set: 17 18 19

Temperature detected: NOW 25.3°

Reduce temperature

Increase temperature

Switch off thermostat

Thermostat options

Help

HELP

OPTIONS

## THERMOSTAT OPTIONS

Temperature set: 13 14 15

Temperature detected: NOW 21.1°

Setup

Programming

Statistics


HELP

OPTIONS

## SETUP SCREEN

- Select the programmable thermostat or programmable thermostats on the main screen and set the away offset for each of them (to a maximum of 5°C)

Away offset setting




Set up screen. In this section you may also set:

- Name of programmable thermostat
- Type of device (heating/cooling)
- Type of control: Hysteresis (0.2°C / 0.4°C / 0.8°C / 1.6°C), PID (10 min. / 15 / 20 / 25 / 30 / 60 min.)
- Descaling pump: in systems with a pump, it is good practice to turn it on periodically to prevent the build up of limestone and consequent seizure. When this function is activated, the programmable thermostat switches on heating 10 minutes a week.
- Away offset: geolocation is used to reduce the set temperature by applying an offset when you are not home.


#### FUNCTIONS ALWAYS ENABLED

- Anti-block function with battery flat: with the battery flat (below 2.4V) the device might not have enough power to switch off heating. With the battery flat, the relay remains at the OFF position.


## SELECT TYPE OF SYSTEM



## TYPE OF CONTROL: HYSTERESIS / PID



## AWAY OFFSET




In case of change of type of operation the programs will be canceled.

Summarised weekly programming screen.  
Press the day to set the daily programming.



## DAILY PROGRAMMING



Daily programming (max 10 programs a day) can be defined for a minimum time of 1 minute and for a minimum temperature step of 0.5°C.

## COPY PROGRAM

← BACK PERRY ☰

TUESDAY

COPY DAYS

USE SAME SCHEDULE ON...

- Sunday
- Monday
- Tuesday
- Wednesday
- Thursday
- Friday
- Saturday

CANCEL COPY

## HELP

← BACK PERRY ☰

TUESDAY

00 22.0° From 00:00h to 01:00h

01

GETTING STARTED

05 11.0° From 04:00h to 07:00h

06


HELP

**Temperatures**


Add up to 9 temperature slots

READY!


### ADD / MODIFY PROGRAM




### TIME SETTING




## DATA DISPLAY




MAIN SCREEN




INSTANTANEOUS CONSUMPTION




SETUP





## DATA DISPLAY






**GETTING STARTED**

**Main menu**  
Click icon to Access **account setup options**

NEXT

● ○ ○ ○ ○ ○  
Skip help





**GETTING STARTED**



**Geolocation**  
**Away** will reduce by default 2°C

NEXT


○ ● ○ ○ ○ ○  
Skip help



On some screens, for example temperature change and programming, the "Help" button shows some specific help functions



## SUPPORT



In case of failed connection, consult the FAQ on page:  
<http://perry.it/prodotto/1tx-cr028wifikit.aspx>

Or else access it using the QR code:



**Important:** the manufacturer shall not, under any circumstances, be liable if the products fail to operate due to the interruption of the internet network or unavailability of these resources: Cloud, Server, Portal.

**Important:** internet access costs are charged to users according to the rates of their mobile phone provider.

## Write down the date of your devices and of your accounts

SMARTBOX CODE

---

---

---

SMARTBOX CODE

---

---

---

SMARTBOX CODE

---

---

---

Find the **Perry Programmable Thermostat** App in stores or take a picture of the QR Code for the operating system which your device uses.



**PERRY ELECTRIC s.r.l.**

Via Milanese, 11

22070 Veniano - CO - ITALY

T. +39 031 8944.1

Fax +39 031 8365201

[www.perry.it](http://www.perry.it) - [venditalia@perry.it](mailto:venditalia@perry.it)



12-24

DERXPE004EN